

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Aqua Design Amano

Supplier's address: Geschäftsführung, Deichstrasse 189, 27804 Berne, DE

Model identifier: ADA Aquasky RGB Basic 450

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	Adapter		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes

Product parameters


Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	31	Energy efficiency class	F
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	2 454 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 800
On-mode power (P_{on}), expressed in W	30,3	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,40
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	81
Outer dimensions without separate control gear, lighting control	Height	71	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	457	
	Depth	135	
			See image in last page

parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,306 0,326
Parameters for directional light sources:			
Peak luminous intensity (cd)	1 214	Beam angle in degrees, or the range of beam angles that can be set	105
Parameters for LED and OLED light sources:			
R9 colour rendering index value	1	Survival factor	1,00
the lumen maintenance factor	0,97		
Parameters for LED and OLED mains light sources:			
displacement factor (cos ϕ_1)	0,95	Colour consistency in McAdam ellipses	5
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-
Flicker metric (Pst LM)	0,2	Stroboscopic effect metric (SVM)	0,1

(a) '-': not applicable;

(b) '-': not applicable;

Spectral Distribution



Model placed on the Union market.



EPREL registration number: 2299207

<https://eprel.ec.europa.eu/qr/2299207>

Supplier: E. A. european aquaristics GmbH (Importer)

Website:

Customer care service:

Name: Geschäftsführung

Website: www.europeanaquaristics.com

Email: j.buhlmann@europeanaquaristics.com

Phone: 015222578750

Address:

Deichstrasse 189
27804 Berne
Germany