Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| sources | | | | |
|--|------------------|------------------------------|--|--------------|
| Supplier's name | e or trade mark: | Chihiros Aquatic Stu | ıdio | |
| Supplier's addre | ess: Nicole Wang | , Einsteinstr.2, 4146 | 4 Neuss, DE | |
| Model identifie | r: All501 | | | |
| Type of light so | urce: | | | |
| Lighting techno | logy used: | LED | Non-directional or directional: | DLS |
| Light source cap (or other electri | • • | External adapter connection | | |
| Mains or non-m | nains: | MLS | Connected light source (CLS): | No |
| Colour-tuneable | e light source: | No | Envelope: | - |
| High luminance | light source: | No | | |
| Anti-glare shield: | | No | Dimmable: | Yes |
| | | Product para | T | |
| Parameter | | Value | Parameter | Value |
| | | General product p | | |
| Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer | | 23 | Energy efficiency class | F |
| Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | | 2 063 in Wide cone (120°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 8 500 |
| On-mode power (P _{on}), expressed in W | | 23,3 | Standby power (P _{sb}), expressed in W and rounded to the second decimal | 0,33 |
| Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal | | - | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set | 83 |
| Outer | Height | 10 | Spectral power | See image |
| dimensions | Width | 485 | distribution in the | in last page |
| without | Depth | 67 | | |

| separate control gear, lighting control parts and non- lighting control parts, | | range 250 nm to 800 nm, at full-load | | | | |
|---|---------------------|--|-------|--|--|--|
| if any (millimetre) | | | | | | |
| Claim of equivalent power ^(a) | - | If yes, equivalent power (W) | - | | | |
| | | Chromaticity coordinates (x and y) | 0,291 | | | |
| Parameters for directional light sources: | | | | | | |
| Peak luminous intensity (cd) | 714 | Beam angle in degrees, or the range of beam angles that can be set | 121 | | | |
| Parameters for LED and OLED light sources: | | | | | | |
| R9 colour rendering index value | 5 | Survival factor | 1,00 | | | |
| the lumen maintenance factor | 0,96 | | | | | |
| Parameters for LED and OLED m | ains light sources: | | | | | |
| displacement factor (cos φ1) | 0,97 | Colour consistency in McAdam ellipses | 0 | | | |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | _(b) | If yes then replacement claim (W) | - | | | |
| Flicker metric (Pst LM) | 0,0 | Stroboscopic effect metric (SVM) | 0,0 | | | |

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;

