## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark:	Chihiros Aquatic Studio
--------------------------------	-------------------------

Supplier's address: Nicole Wan, Einsteinstr.2, Neuss, 41464 Neuss Neuss, DE

Model identifier: Tiny terrarium egg

_	•			
Type	Λt	liont	COLL	rca.
IVDC	v	HIGHL	30 U	ı cc.

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	External adapter		
(or other electric interface)	connection		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes
Product parameters			

Product parameters				
Parameter		Value	Parameter	Value
	General product parameters:			
	nption in on- 00 h), rounded st integer	10	Energy efficiency class	F
dicating if it refe a sphere (360°)	s flux (фuse), in- ers to the flux in , in a wide cone errow cone (90º)	900 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	9 000
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	10,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,43
(P <sub>net</sub> ) for CLS, 6	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimen-	Height	2 410	Spectral power dis-	See image
sions without	Width	1 630	tribution in the	in last page
separate control gear, lighting control	Depth	1 630	range 250 nm to 800 nm, at full-load	

parts and non- lighting con- trol parts, if any (millime- tre)			
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,292 0,286
Parameters for LED and OLED I	ight sources:		
R9 colour rendering index value	12	Survival factor	1,00
the lumen maintenance factor	0,90		
Parameters for LED and OLED r	mains light sources:		
displacement factor (cos φ1)	0,59	Colour consistency in McAdam ellipses	0
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	t	If yes then replace- ment claim (W)	-
Flicker metric (Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,0

(a)'-': not applicable; (b)'-': not applicable;

